AABC Commissioning Group

AIA Provider Number 50111116





What is Integrated System Testing for Fire Protection and Life Safety Systems, and how will it affect building commissioning?

Shawn Mahoney, PE National Fire Protection Association

April 17, 2019





IT'S A BIG WORLD. LET'S PROTECT IT TOGETHER.®

Credit(s) earned on completion of this course will be reported to AIA CES for AIA members.
Certificates of Completion for both AIA members and non-AIA members are available upon request.

CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.

This course is registered with AIA





Course Description

What is Integrated System Testing for Fire Protection and Life Safety Systems? Why is it so critical now? How will the requirements for integrated system testing affect you? We will discuss how NFPA 4; The Standard for Integrated Fire Protection and Life Safety System Testing was developed to address a gap in the codes and standards process dealing with confirmation of system integration. We will identify the types of buildings that require integrated system testing and what model codes will require testing to be completed. Finally, you will learn who is involved in integrated system testing and how you can either benefit, or be burned by the new requirements.





Learning Objectives

At the end of the this course, participants will be able to:

- 1 Understand how the integrated system testing process fits into building commissioning and energy management.
- 2 Identify the major codes that include NFPA 4 as a referenced document
- 3 Identify the various members of an integrated system testing team and their roles and responsibilities
- 4 Summarize the test scenarios, testing frequencies, and documentation required by NFPA 4



Closing the Gap






Documentation in Buildings Today



- Engineering Affidavits
- Contractor Affidavits
- Architect Affidavits
- Inspectional Services Department signoffs
- Fire Department signoffs
- Fire Alarm third party test company
- Generator installer w/manufacturer

- Elevator installer w/State inspector
- Electrical installer w/ test company
- Sprinkler installer test reports
- HVAC installer, TAB and CA
- Security installer (e.g., MAC systems)
- BMS building management system installer








NFPA 4: Overview

- Terminology
- Goals/Purpose





NFPA 4: Integrated Testing Team






NFPA 4: Test Scenarios







NFPA 4: Test Frequencies





NFPA 4: Documentation

				System Outputs																
				Fire Alarm Control Center									Notifi	cation	Other Required Fire Safety					
Notes: 1. Five-story office building, use Group B. Cafeteria (use Group A) on first floor equipped with an ansul system. Computer room on third floor equipped with a preaction system. 2. Upon activation of elevator recall the elevator should stop at primary recall floor. If fire is on primary recall floor the elevator should stop at an alternate recall floor. Primary and alternate recall floor should be coordinated with the fire department. 3. Shutdown of mechanical equipment should be interfaced with building automation system.					Actuate auditte alarm signal	Actuate common supervisory signal indicator	Actuate auditie supervisory signal	Actuate common trouble signal indicator	Actuate auditie trouble signal	Display and printchange of status and time of initiating event	Transmit alarm to fire department and to central station — masterbox	Ilum hate ass colated detector LED indicator	Actuate associated exterior fire alarm beacon(s)	Actuate all exacuation signals for the building	Release all magnetically held doors	Recall associated elevator in accordance with recall sequence (see Note 2)	Shut down associated mechanical equipment (see Note 3)	Release preætion valve (charge sprinklers)	Elevator hoistway vent open	
	_		Trains are and will shall be found as he had a few	A	В	С	D	E	F	G	H X	Ţ	J	K	L X	М	N	0	Р	1
		1	Typical manual pull station (by device) — levels 1-5	Х	Х				_	X	1000	8	1000	X	- 1000				- 10	+
	-	2	Typical elevator recall smoke detector (by device) — by floor (lobby)	Х	Х					X	Х		Х	X	Х	X			X	+
اء	Fre Alarm Inputs	3	Elevator machine room smoke detector	Х	Х			_		Х	Х	Х	Х	Х	Х	-			Х	1
System		4	Typical smoke detector (by device) — computer room (third floor) — preaction system	х	X					Х	Х		х	Х	Х				-	1
Fire Alarm S		5	Typical wet sprinkler system flow control valve assembly flow switch — by floor	Х	X				X	Х	Х		Х	Х	Х	_			-	1
	Ala	6	Typical wet sprinkler system flow control valve assembly tamper switch — by floor			Х	х			Х										
	Ē	7	Typical preaction sprinkler system flow control valve assembly flow switch — by floor	х	Х				х	Х	х			х	х					
		8	Typical preaction sprinkler system flow control valve assembly tamper switch — by floor			X	×			х						3				
	I	9	Kitchen cafeteria ansul system — first floor	х	x					х	х				х				х	Ī
		10	Typical duct-in smoke detector (by device) — by floor							х							х			Ī
		11	Fire pump running			×	х			х						100				1
- [:	<u>6</u>	12	Fire pump power failure			х	х			х										1



NFPA 4: Why Now



9.11.4 Integrated Fire Protection and Life Safety System Tests.

9.11.4.1 Basic Testing.

Where required by Chapters 11 through 43, installations involving two or more integrated fire protection or life safety systems shall be tested to verify the proper operation and function of such systems in accordance with 9.11.4.1.1 and 9.11.4.1.2.

9.11.4.1.1

When a fire protection or life safety system is tested, the response of integrated fire protection and life safety systems shall be verified.

9.11.4.1.2

After repair or replacement of equipment, required retesting of integrated systems shall be limited to verifying the response of fire protection or life safety functions initiated by repaired or replaced equipment.

9.11.4.2 * NFPA 4 Testing.

Where required by 9.3.5 or Chapters 11 through 43, the following integrated fire protection and life safety systems shall be tested in accordance with 9.11.4.1 and 9.11.4.2.1 through 9.11.4.2.2:


- (1) Integrated fire protection and life safety systems in high-rise buildings
- (2) Integrated fire protection and life safety systems that include a smoke control system


9.11.4.2.1

For new buildings, integrated testing in accordance with NFPA 4 shall be conducted prior to the issuance of a certificate of occupancy.

9.11.4.2.2

For existing buildings, integrated testing in accordance with NFPA 4 shall be conducted at intervals not exceeding 10 years unless otherwise specified by an integrated system test plan prepared in accordance with NFPA 4.





NFPA 4: Why Now





901.6.2 Integrated testing.

Where two or more fire protection or life safety systems are interconnected, the intended response of subordinate fire protection and life safety systems shall be verified when required testing of the initiating system is conducted. In addition, integrated testing shall be performed in accordance with Sections 901.6.2.1 and 901.6.2.2.

901.6.2.1 High-rise buildings.

For high-rise buildings, integrated testing shall comply with NFPA 4, with an integrated test performed prior to issuance of the certificate of occupancy and at intervals not exceeding 10 years, unless otherwise specified by an integrated system test plan prepared in accordance with NFPA 4. If an equipment failure is detected during integrated testing, a repeat of the integrated test shall not be required, except as necessary to verify operation of fire protection or life safety functions that are initiated by equipment that was repaired or replaced.


901.6.2.2 Smoke control systems.


Where a fire alarm system is integrated with a smoke control system as outlined in Section 909, integrated testing shall comply with NFPA 4, with an integrated test performed prior to issuance of the certificate of occupancy and at intervals not exceeding 10 years, unless otherwise specified by an integrated system test plan prepared in accordance with NFPA 4. If an equipment failure is detected during integrated testing, a repeat of the integrated test shall not be required, except as necessary to verify operation of fire protection or life safety functions that are initiated by equipment that was repaired or replaced.

NFPA 4: Future

- A2020 Revision Cycle
- Public Comment Date: February 22nd May 8th 2019











NFPA 4: Resources


NFPA 4, Integrated Systems Testing Fundamentals Training

Rosemont, IL April 25, 2019

Tarrytown, NY May 23, 2019

Visit <u>nfpa.org/4classroom</u> to learn more and register.

Free online tutorial and other resources at nfpa.org/4





This concludes The American Institute of Architects Continuing Education Systems Course

Shawn Mahoney smahoney@nfpa.org





